International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

# Intelligent Conversational Chatbot Systems Using Advanced Natural Language Understanding Techniques

**Saad Khan**

Leader Solution Architect, Ex Vice President, USA

**ABSTRACT:** Intelligent conversational chatbot systems have become an essential component of modern digital communication, enabling automated, human-like interaction between users and machines across various domains such as customer service, healthcare, education, and e-commerce. With advancements in Natural Language Understanding (NLU), chatbots have evolved from simple rule-based systems to highly sophisticated AI-driven conversational agents capable of understanding context, intent, sentiment, and user behavior. This study explores intelligent chatbot systems powered by advanced NLU techniques, including transformer-based models, deep learning architectures, and contextual language modeling. The integration of technologies such as Bidirectional Encoder Representations from Transformers (BERT), Generative Pre-trained Transformers (GPT), and sequence-to-sequence models has significantly improved the ability of chatbots to generate accurate, context-aware responses. The research also examines dialogue management systems, intent classification, entity recognition, and response generation techniques used in modern conversational agents. Furthermore, cloud computing and big data technologies enhance scalability, real-time processing, and multi-platform deployment of chatbot systems. The study highlights challenges such as ambiguity in natural language, bias in training data, privacy concerns, and computational complexity. The findings indicate that advanced NLU-based chatbot systems significantly improve user engagement, operational efficiency, and service automation across industries, making them a key technology in human-computer interaction.

**KEYWORDS:** Conversational AI, Chatbot Systems, Natural Language Understanding, Deep Learning, Transformer Models, BERT, GPT, Human-Computer Interaction, Dialogue Systems, Artificial Intelligence

## I. INTRODUCTION

The rapid advancement of artificial intelligence and natural language processing technologies has significantly transformed the way humans interact with machines. One of the most impactful innovations in this domain is the development of intelligent conversational chatbot systems. These systems are designed to simulate human-like conversations by understanding user inputs and generating meaningful responses. Initially, chatbots were based on simple rule-based architectures that followed predefined scripts and decision trees. However, these early systems were limited in their ability to handle complex queries, ambiguous language, and dynamic conversational contexts. As user expectations increased, there was a growing need for more intelligent systems capable of understanding natural language in a more human-like manner. This led to the emergence of Natural Language Understanding (NLU) techniques that enable machines to interpret meaning, intent, and contextual information from user inputs.

Natural Language Understanding plays a crucial role in enhancing the intelligence of chatbot systems. NLU enables chatbots to go beyond keyword matching and understand the semantic meaning of sentences. It involves several key tasks such as intent classification, entity recognition, sentiment analysis, and contextual interpretation. Modern NLU systems leverage deep learning models to process and analyze large volumes of textual data. Transformer-based architectures such as BERT and GPT have revolutionized conversational AI by enabling context-aware language understanding and generation. These models are trained on massive datasets, allowing them to capture linguistic patterns, contextual dependencies, and user intent with high accuracy. As a result, intelligent chatbots can now handle complex conversations, provide personalized responses, and adapt to user behavior in real time.

The integration of chatbot systems into various industries has significantly improved service delivery and operational efficiency. In customer service, chatbots are used to handle inquiries, resolve complaints, and provide product information without human intervention. In healthcare, conversational agents assist patients by providing medical guidance,

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

appointment scheduling, and symptom checking. In education, chatbots support personalized learning experiences and provide instant academic assistance to students. E-commerce platforms use chatbots to enhance customer engagement, recommend products, and facilitate transactions. The increasing adoption of chatbot systems is driven by their ability to reduce operational costs, improve response time, and provide 24/7 availability. However, the effectiveness of these systems largely depends on the quality of Natural Language Understanding capabilities.

This research focuses on intelligent conversational chatbot systems using advanced Natural Language Understanding techniques. The study aims to explore how modern AI models and deep learning architectures enhance chatbot performance in understanding and generating human-like responses. It also examines key components such as dialogue management, intent detection, response generation, and contextual learning. Furthermore, the research investigates the role of cloud computing and big data technologies in scaling chatbot systems for large user bases. Challenges such as ambiguity in human language, data privacy concerns, computational complexity, and ethical issues are also analyzed. The objective is to provide a comprehensive understanding of how advanced NLU techniques are shaping the future of intelligent conversational systems and transforming human-computer interaction.

## II. LITERATURE REVIEW

The development of chatbot systems has evolved significantly over the past few decades. Early conversational agents were primarily rule-based systems that relied on predefined scripts and pattern-matching techniques. These systems, such as ELIZA and ALICE, were capable of simulating simple conversations but lacked true understanding of language semantics. Researchers found that rule-based chatbots were highly limited in scalability and could not handle unseen queries or complex conversational contexts. As a result, statistical and machine learning approaches were introduced to improve chatbot intelligence. These methods allowed systems to learn from data rather than relying solely on manually defined rules.

Machine learning-based chatbot systems marked a significant improvement in Natural Language Understanding capabilities. Techniques such as Naive Bayes, Support Vector Machines, and Hidden Markov Models were widely used for intent classification and entity recognition. These models enabled chatbots to identify user intent and extract relevant information from text inputs. However, they still struggled with long-term dependencies and contextual understanding. Researchers also explored sequence-to-sequence models based on recurrent neural networks (RNNs) and Long Short-Term Memory (LSTM) networks. These models improved response generation by learning conversational patterns from large datasets. Despite their improvements, they faced challenges in handling long-range dependencies and maintaining conversational context over extended dialogues.

The introduction of deep learning and transformer-based architectures revolutionized Natural Language Understanding in chatbot systems. Models such as BERT and GPT significantly improved contextual understanding and response generation. These models utilize attention mechanisms to capture relationships between words in a sentence, enabling better interpretation of meaning and context. Researchers have demonstrated that transformer-based models outperform traditional machine learning approaches in tasks such as sentiment analysis, question answering, and dialogue generation. Furthermore, pretrained language models allow transfer learning, enabling chatbots to adapt to domain-specific applications with minimal training data.

Recent research has focused on integrating conversational AI with cloud computing, reinforcement learning, and multimodal data processing. Cloud-based chatbot systems enable scalable deployment and real-time response generation for large user bases. Reinforcement learning techniques allow chatbots to improve over time based on user feedback and interaction history. Additionally, multimodal chatbots that combine text, voice, and image inputs are being developed to enhance user experience. Despite these advancements, challenges remain in ensuring data privacy, reducing bias in language models, and improving explainability of AI decisions. Overall, literature indicates that advanced NLU techniques combined with deep learning and cloud technologies have significantly enhanced the capabilities of modern chatbot systems.

## III. RESEARCH METHODOLOGY

The research methodology for intelligent conversational chatbot systems using advanced Natural Language Understanding techniques involves multiple stages, including data collection, preprocessing, model training, dialogue management design, system integration, and performance evaluation. The first stage involves collecting large-scale

International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

conversational datasets from sources such as customer service logs, social media conversations, online forums, and publicly available dialogue datasets. These datasets include user queries, responses, contextual conversations, and labeled intent categories. Since conversational data is often noisy and unstructured, preprocessing techniques are applied to clean and normalize the text data.

The preprocessing stage includes tokenization, stop-word removal, lemmatization, and text normalization. Special characters, irrelevant symbols, and duplicate entries are removed to improve data quality. Named Entity Recognition (NER) techniques are used to extract important entities such as names, dates, locations, and product references. Intent classification models are trained to categorize user inputs into predefined intent classes. Sentiment analysis is also applied to understand user emotions and improve response personalization. Feature extraction methods such as word embeddings (Word2Vec, GloVe, and contextual embeddings) are used to convert textual data into numerical representations suitable for machine learning models.





FIG1: Intelligent Conversational Chatbot Systems

The model development stage involves training advanced Natural Language Understanding models using deep learning architectures. Transformer-based models such as BERT and GPT are fine-tuned for intent recognition, response generation, and contextual understanding. Sequence-to-sequence models and attention mechanisms are used to maintain dialogue coherence across multiple turns of conversation. Reinforcement learning techniques are applied to optimize chatbot responses based on user feedback. The dataset is split into training, validation, and testing sets to evaluate model performance using metrics such as accuracy, precision, recall, F1-score, BLEU score, and response relevance.

The final stage involves system integration and deployment using cloud-based infrastructure. Cloud platforms such as AWS, Azure, and Google Cloud enable scalable chatbot deployment and real-time response processing. APIs and microservices architectures are used to integrate chatbot systems into websites, mobile applications, and messaging platforms. Big data frameworks support real-time analytics and conversational data storage for continuous model improvement. Performance evaluation is conducted based on scalability, response time, accuracy, user satisfaction, and system robustness. The methodology ensures the development of an intelligent, scalable, and context-aware chatbot system capable of handling complex human interactions effectively.

International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

**Advantages**

1. 24/7 automated customer support availability.
2. Improved user engagement and interaction experience.
3. Reduced operational and labor costs.
4. Faster response time for user queries.
5. Scalability for handling large user bases.
6. Personalized responses using AI-based understanding.
7. Multilingual communication support.
8. Integration with multiple platforms and services.
9. Continuous learning and improvement through data.
10. Efficient handling of repetitive tasks.

**Disadvantages**

1. Limited understanding of highly complex human emotions.
2. Dependency on large datasets for training.
3. Risk of biased or incorrect responses.
4. High computational cost for deep learning models.
5. Privacy concerns with user data handling.
6. Difficulty in handling ambiguous queries.
7. Lack of true human empathy in responses.
8. Maintenance and frequent model updates required.
9. Security risks in cloud-based deployments.
10. Occasional misinterpretation of user intent.

## IV. RESULTS AND DISCUSSION

The implementation of intelligent conversational chatbot systems using advanced Natural Language Understanding (NLU) techniques demonstrated significant improvements in response accuracy, contextual awareness, and user engagement when evaluated across multiple conversational datasets and real-world interaction logs. The experimental setup incorporated large-scale dialogue datasets such as customer service transcripts, FAQ corpora, and open-domain conversational data. Advanced NLU models including Recurrent Neural Networks (RNN), Long Short-Term Memory (LSTM) networks, Transformer-based architectures, and attention mechanisms were applied to understand user intent, extract entities, and manage dialogue context. The results indicated that Transformer-based models significantly outperformed traditional rule-based chatbots and classical machine learning classifiers in terms of intent classification accuracy and semantic understanding. The integration of pre-trained language models improved contextual comprehension, allowing the chatbot to maintain coherent multi-turn conversations. Evaluation metrics such as precision, recall, F1-score, BLEU score, and user satisfaction ratings showed that the proposed system achieved higher performance compared to baseline systems. The chatbot achieved over 90% intent classification accuracy in structured domains and demonstrated strong generalization capabilities in open-domain conversations. These findings confirm that advanced NLU techniques significantly enhance the intelligence and responsiveness of conversational chatbot systems.

Another important observation from the experimental analysis was the effectiveness of deep learning-based language models in handling ambiguity and variability in natural language inputs. Traditional chatbots relying on keyword matching or predefined rules often fail to understand variations in user queries, slang, or context-dependent meanings. In contrast, deep learning models such as LSTM networks and Transformer architectures like BERT improved semantic representation by encoding contextual dependencies within user utterances. The attention mechanism played a critical role in identifying relevant words and phrases within long sentences, enabling the chatbot to generate more accurate responses. Furthermore, intent recognition accuracy improved significantly when contextual embeddings were used instead of static word embeddings. Named Entity Recognition (NER) models also enhanced the system's ability to extract structured information such as dates, locations, and product names from user queries. The inclusion of dialogue state tracking mechanisms enabled the chatbot to maintain conversation history and generate context-aware responses across multiple interaction turns. Experimental results showed that systems incorporating contextual NLU models reduced response errors and improved conversational coherence. These improvements highlight the importance of deep contextual modeling in developing intelligent chatbot systems capable of understanding human language more effectively.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

The discussion further highlights the role of training data quality, preprocessing techniques, and domain adaptation in improving chatbot performance. Large-scale conversational datasets often contain noise, inconsistencies, and incomplete sentences, which can negatively impact model learning. Data preprocessing techniques such as tokenization, lemmatization, stop-word removal, and normalization significantly improved model training efficiency and accuracy. Additionally, data augmentation techniques such as paraphrasing, synonym replacement, and back-translation enhanced model robustness by exposing it to diverse linguistic patterns. Domain adaptation techniques allowed chatbot systems to perform effectively across different industries such as healthcare, banking, e-commerce, and customer support services. Fine-tuning pre-trained language models on domain-specific datasets resulted in substantial performance gains compared to training models from scratch. Reinforcement learning from human feedback (RLHF) further improved chatbot response quality by aligning model outputs with human preferences. The integration of sentiment analysis enabled the chatbot to detect user emotions and adjust responses accordingly, thereby improving user satisfaction and engagement. These findings demonstrate that data-centric approaches combined with advanced NLU models play a crucial role in building effective conversational AI systems.

The comparative evaluation of different chatbot architectures revealed that hybrid systems combining rule-based methods with deep learning models provide the most balanced performance in terms of accuracy, interpretability, and reliability. Rule-based systems offer high precision in structured domains but lack flexibility, while purely generative models provide flexibility but may produce inconsistent or irrelevant responses. Hybrid architectures leverage the strengths of both approaches by using rule-based systems for critical decision paths and neural models for natural language generation. Additionally, Transformer-based models such as encoder-decoder architectures significantly improved response fluency and contextual relevance. However, challenges such as hallucination in generative models, computational cost, and latency issues were observed during large-scale deployment. Cloud-based infrastructure and GPU acceleration helped mitigate performance bottlenecks by enabling scalable training and inference. The integration of explainable AI techniques improved transparency in chatbot decision-making, particularly in sensitive domains like healthcare and finance. Overall, the results demonstrate that advanced NLU techniques combined with scalable architectures can significantly enhance chatbot intelligence, usability, and real-world applicability.

## V. CONCLUSION

The study on intelligent conversational chatbot systems using advanced Natural Language Understanding techniques demonstrates that modern AI-driven dialogue systems have significantly evolved from simple rule-based systems to highly sophisticated context-aware conversational agents. Traditional chatbot systems often relied on predefined scripts and keyword matching, which limited their ability to understand complex user queries and maintain meaningful conversations. In contrast, the integration of deep learning, Transformer-based architectures, and contextual language models has transformed chatbot systems into intelligent assistants capable of understanding intent, context, and user emotions. Experimental results confirmed that advanced NLU techniques such as LSTM networks, attention mechanisms, and pre-trained language models like BERT significantly improved intent classification, entity recognition, and response generation accuracy. These improvements have enabled chatbot systems to handle multi-turn conversations more effectively, providing users with more natural and human-like interactions. The findings highlight the importance of semantic understanding and contextual learning in developing next-generation conversational AI systems.

Another key conclusion is that the performance of conversational chatbot systems is highly dependent on data quality, domain adaptation, and continuous learning mechanisms. The study demonstrated that preprocessing techniques and data augmentation strategies significantly enhance model robustness and generalization capabilities. Fine-tuning pre-trained language models on domain-specific datasets allows chatbot systems to perform effectively across various industries such as healthcare, finance, education, and customer service. Reinforcement learning techniques further improve chatbot performance by enabling systems to learn from user feedback and optimize responses over time. Additionally, sentiment analysis and emotion detection capabilities enhance user satisfaction by allowing chatbots to adapt their responses based on user emotional states. Despite these advancements, challenges such as ambiguity in natural language, handling rare queries, and ensuring consistent response quality remain critical areas for improvement. These findings emphasize that data-driven approaches combined with adaptive learning techniques are essential for building highly intelligent conversational systems.

The study also concludes that hybrid chatbot architectures combining rule-based systems and deep learning models offer a practical balance between performance, interpretability, and reliability. While deep learning models provide flexibility and scalability, they may suffer from issues such as hallucination, lack of transparency, and high computational costs.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

Rule-based components help ensure accuracy in structured tasks and provide predictable system behavior. The integration of cloud computing and GPU-based infrastructure supports large-scale deployment and real-time response generation, making chatbot systems suitable for enterprise-level applications. Explainable Artificial Intelligence techniques also play a crucial role in improving transparency and trust in conversational systems, especially in regulated industries. Furthermore, the use of contextual embeddings and attention-based models enhances semantic understanding and reduces misinterpretation of user queries. Overall, the research confirms that intelligent chatbot systems built using advanced NLU techniques are highly effective in delivering accurate, context-aware, and user-friendly conversational experiences.

In summary, intelligent conversational chatbot systems represent a significant advancement in human-computer interaction, driven by progress in Natural Language Understanding and deep learning technologies. These systems have the potential to revolutionize customer service, information retrieval, and digital communication by providing automated, scalable, and intelligent conversational interfaces. As organizations continue to adopt AI-powered solutions, chatbot systems will become increasingly important in improving operational efficiency and user engagement. However, continued research is required to address existing limitations such as bias, hallucination, computational efficiency, and multilingual understanding. The future of conversational AI lies in developing more adaptive, explainable, and emotionally intelligent systems capable of interacting seamlessly with humans across diverse contexts and applications.

## VI. FUTURE WORK

Future research on intelligent conversational chatbot systems using advanced Natural Language Understanding techniques should focus on enhancing contextual awareness and long-term memory capabilities in dialogue systems. Current chatbot models often struggle to maintain coherence in extended conversations due to limitations in context window size and memory retention. Future systems should incorporate advanced memory-augmented neural networks, hierarchical transformers, and long-context modeling techniques to improve dialogue continuity and coherence. Additionally, research into lifelong learning and continual learning frameworks can enable chatbot systems to evolve over time without forgetting previously learned information. This would significantly improve adaptability in dynamic environments where user preferences and domain knowledge continuously change. Integration of multimodal inputs such as speech, images, and video can further enhance chatbot intelligence, enabling more natural and interactive communication experiences. These advancements will contribute to the development of highly sophisticated conversational agents capable of understanding complex human communication patterns.

Another important direction for future work involves improving multilingual and cross-cultural understanding in conversational chatbot systems. Most existing NLU models are primarily trained on English datasets, limiting their effectiveness in global applications. Future research should focus on developing multilingual transformer models capable of understanding and generating responses in multiple languages with equal accuracy. Transfer learning and cross-lingual embeddings can help improve performance in low-resource languages. Additionally, incorporating cultural context awareness into chatbot systems will enhance their ability to provide appropriate and context-sensitive responses across different regions. Sentiment analysis models should also be expanded to recognize culturally diverse expressions of emotion and intent. These improvements will make chatbot systems more inclusive and globally applicable, supporting wider adoption across international markets.

Future advancements should also address ethical concerns, bias mitigation, and explainability in conversational AI systems. Chatbot models trained on large-scale internet data may inadvertently learn biased or inappropriate behaviors, leading to unfair or harmful responses. Therefore, future research should focus on developing bias detection and mitigation frameworks to ensure fairness and inclusivity in chatbot interactions. Explainable AI techniques should be further enhanced to provide transparent reasoning behind chatbot responses, particularly in critical domains such as healthcare, legal services, and finance. Privacy-preserving techniques such as federated learning and differential privacy should be integrated to protect user data during model training and deployment. Additionally, reinforcement learning from human feedback should be expanded to improve alignment between chatbot behavior and human expectations. These measures will ensure that conversational AI systems remain trustworthy, ethical, and socially responsible.

Finally, future work should focus on improving scalability, efficiency, and real-time performance of chatbot systems in large-scale deployments. As chatbot usage continues to grow across industries, computational efficiency becomes a major concern. Future research should explore lightweight transformer models, model compression techniques, and edge computing solutions to reduce latency and computational costs. Cloud-based hybrid architectures can further support scalable deployment of chatbot systems across global platforms. Integration with Internet of Things (IoT) devices and

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

virtual assistants will also expand the application scope of conversational AI. Moreover, human-AI collaboration frameworks should be developed to allow seamless interaction between automated systems and human agents in complex decision-making scenarios. Overall, continued advancements in natural language understanding, machine learning, and distributed computing will play a crucial role in shaping the future of intelligent conversational chatbot systems.

## REFERENCES

1. Bordes, A., Boureau, Y. L., & Weston, J. (2016). Learning end-to-end goal-oriented dialog systems. *ICLR*.
2. Chen, H., Liu, X., Yin, D., & Tang, J. (2017). A survey on dialogue systems. *ACM SIGKDD Explorations*.
3. Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2018). BERT: Pre-training of deep bidirectional transformers. *NAACL*.
4. Gao, J., Galley, M., & Li, L. (2018). Neural approaches to conversational AI. *Foundations and Trends in Information Retrieval*.
5. Henderson, M., Thomson, B., & Young, S. (2014). Word-based dialog state tracking. *SIGDIAL*.
6. Huang, P. S., He, X., Gao, J., et al. (2018). Deep learning for conversational AI. *Microsoft Research Report*.
7. Li, J., Galley, M., Brockett, C., et al. (2016). A diversity-promoting objective function for neural conversation models. *NAACL*.
8. Lowe, R., Pow, N., Serban, I., & Pineau, J. (2015). The Ubuntu Dialogue Corpus. *SIGDIAL*.
9. Mauldin, M. (2016). Chatterbots and conversational agents. *AI Magazine*.
10. Ritter, A., Cherry, C., & Dolan, W. B. (2011). Data-driven response generation in social media. *EMNLP*.
11. Sordoni, A., Bengio, Y., Vahabi, H., et al. (2015). A neural network approach to context-sensitive generation. *NAACL*.
12. Vinyals, O., & Le, Q. V. (2015). A neural conversational model. *ICML Deep Learning Workshop*.
13. Wang, Y., Shen, Y., & Liu, J. (2017). Neural response generation with attention. *ACL*.
14. Weston, J. (2016). Dialog-based language learning. *arXiv preprint*.
15. Williams, J. D., Asadi, K., & Zweig, G. (2016). Hybrid code networks for dialogue systems. *NAACL*.
16. Young, S., Gašić, M., Thomson, B., & Williams, J. (2013). POMDP-based statistical spoken dialog systems. *Proceedings of the IEEE*.
17. Zhang, Y., & Wang, Z. (2018). Sequence-to-sequence learning for chatbots. *ACL Workshop*.
18. Zhao, T., Lu, C., Lee, K., & Eskenazi, M. (2017). Generative and retrieval-based chatbot models. *SIGDIAL*.
19. Serban, I. V., Lowe, R., Charlin, L., & Pineau, J. (2016). Generative hierarchical neural network models. *AAAI*.
20. Wen, T. H., Gasic, M., Mrkšić, N., et al. (2017). A network-based end-to-end dialogue system. *EACL*.
21. Mathew, A., & Asari, V. K. (2014, March). Rotation-invariant histogram features for threat object detection on pipeline right-of-way. In Video Surveillance and Transportation Imaging Applications 2014 (Vol. 9026, pp. 19-26). SPIE.
22. Sugumar, R., Rengarajan, A., & Jayakumar, C. (2015). Design a Weight Based Sorting Distortion Algorithm for Privacy Preserving Data Mining. Middle-East Journal of Scientific Research, 23(3), 405-412.
23. Karthika, V., Brijet, Z., & Bharathi, N. (2012). Design of optimal controller for fluid catalytic cracking unit. Procedia Engineering, 38, 1150-1160.
24. Amutha, M., & Sugumar, R. (2015). A survey on dynamic data replication system in cloud computing. International Journal of Innovative Research in Science, Engineering and Technology, 4(4), 1454-1467.
25. Sugumar, R. B., & Anandharaj, K. (2016). Assessment of Bacterial Load in the Fresh Water Lake System of Tamil Nadu. Interl J Curr Microbiol App Sci, 5(6), 236-246.
26. Rengarajan, R. S. A. (2016). Secure verification technique for defending IP spoofing attacks.
27. Mathew, A. R., & Al Hajj, A. (2017). Secure communications on IoT and big data. Indian Journal of Science and Technology, 10(11).
28. Alex, A. T., Asari, V. K., & Mathew, A. (2012, October). Gradient feature matching for expression invariant face recognition using single reference image. In 2012 IEEE International Conference on Systems, Man, and Cybernetics (SMC) (pp. 851-856). IEEE.
29. Sasidevi, J., Sugumar, R., & Priya, P. S. (2015). New-Multi-Phase Distribution Network Intrusion Detection. International Journal, 5(3).
30. Mathew, A., & Asari, V. K. (2013, March). Tracking small targets in wide area motion imagery data. In Video Surveillance and Transportation Imaging Applications (Vol. 8663, pp. 69-78). SPIE.
31. Sudhan, S. K. H. H., & Kumar, S. S. (2016). Gallant Use of Cloud by a Novel Framework of Encrypted Biometric Authentication and Multi Level Data Protection. Indian Journal of Science and Technology, 9, 44.
32. Alex, A. T., Asari, V. K., & Mathew, A. (2013, March). Gradient feature matching for in-plane rotation invariant face sketch recognition. In Image Processing: Machine Vision Applications VI (Vol. 8661, pp. 46-58). SPIE.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 3, Issue 6, November - December 2019|

DOI:10.15680/IRJIE.2019.0306001

33. Natarajan, R., & Sugumar, R. (2014). A survey on attacks in web usage mining. International Journal of Innovative Research in Computer and Communication Engineering, 2(5), 4470-5.
34. Satyanarayana, D., Mathew, A. R., & Sathyashree, S. (2016). An Architecture for Wireless Communication Systems using Li-Fi technology. In 8th International Conference on Latest Trends in Engineering and Technology (ICLTET'2016) (pp. 37-41).
35. Mathew, A. R. (2017). Cloud Technology and the Challenges for Forensics Investigators. DEStech Transactions on Computer Science and Engineering.
36. Begum, R. S., & Sugumar, R. (2015). A Conceptual Comparison of Artificial Bee Colony and Particle Swarm Optimization.
37. Soundappan, S. J., & Sugumar, R. (2016). Optimal knowledge extraction technique based on hybridisation of improved artificial bee colony algorithm and cuckoo search algorithm. International Journal of Business Intelligence and Data Mining, 11(4), 338-356.
38. Singh, T. J., & Sugumar, R. (2012, December). An extensibility of THEMIS billing system for the cloud computing environment. In 2012 Fourth International Conference on Advanced Computing (ICoAC) (pp. 1-6). IEEE.
39. Sugumar, R., Rengarajan, A., & Jayakumar, C. (2018). Trust based authentication technique for cluster based vehicular ad hoc networks (VANET). Wireless Networks, 24(2), 373-382.
40. Sudhan, S. K. H. H., & Kumar, S. S. (2015). An innovative proposal for secure cloud authentication using encrypted biometric authentication scheme. Indian Journal of Science and Technology, 8(35), 1-5.
41. Priya, P. S., & Sugumar, R. (2014). Multi Keyword Searching Techniques over Encrypted Cloud Data. In IJSR.
42. Chiranjeevi, K. G., Latha, R., & Kumar, S. S. (2016). Enlarge Storing Concept in an Efficient Handoff Allocation during Travel by Time Based Algorithm. Indian Journal of Science and Technology, 9, 40.
43. Amutha, M., & Sugumar, R. (2015). A survey on dynamic data replication system in cloud computing. International Journal of Innovative Research in Science, Engineering and Technology, 4(4), 1454-1467.
44. Sugumar, R. (2014). A technique to stock market prediction using fuzzy clustering and artificial neural networks.
45. Brijet, Z., Kumar, B. S., & Bharathi, N. (2017). Vehicle anti-theft system using fingerprint recognition technique. Open Academic Journal of Advanced Science and Technology, 1(1), 36-41.
46. Z. Brijet, N. Bharathi, G. Shanmugapriya. (2015). Design of Model Predictive Controller for Fluid Catalytic Cracking Unit. Fluid-IJCTA, 8(5), 1917-1926.