International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

Generative Adversarial Network Models for Synthetic Medical Data Generation and Augmentation

Hemlatha Kaur Saran

Researcher, India

ABSTRACT: The scarcity, imbalance, and privacy constraints of medical datasets remain major challenges in developing robust machine learning systems for healthcare applications. Generative Adversarial Networks (GANs) have emerged as a powerful deep learning framework capable of synthesizing realistic medical data, including medical images, electronic health records (EHRs), and physiological signals. This study explores the application of GAN-based models for synthetic medical data generation and data augmentation to improve diagnostic accuracy, model generalization, and privacy preservation.

GANs consist of a generator and discriminator network engaged in an adversarial training process, enabling the generation of highly realistic synthetic samples that resemble real patient data. In the medical domain, variants such as Conditional GANs (cGANs), CycleGANs, and Wasserstein GANs (WGANs) have demonstrated effectiveness in generating high-quality imaging data such as MRI, CT scans, and X-rays, as well as structured tabular clinical data.

This paper provides a comprehensive review of GAN architectures applied to medical data, examines their strengths and limitations, and proposes a methodological framework for implementing GAN-based augmentation pipelines. The study also highlights challenges such as mode collapse, data privacy risks, and evaluation difficulties. Overall, GAN-based synthetic data generation presents a promising direction for enhancing AI-driven healthcare systems while addressing critical data availability constraints.

KEYWORDS: Generative Adversarial Networks, Synthetic Medical Data, Data Augmentation, Deep Learning, Medical Imaging, Privacy Preservation, Conditional GAN, WGAN, Healthcare AI, Machine Learning

I. INTRODUCTION

The healthcare industry is increasingly dependent on data-driven decision-making systems powered by artificial intelligence and machine learning. However, one of the most significant barriers to developing effective AI models in healthcare is the limited availability of high-quality, annotated medical data. Medical datasets are often small, imbalanced, and difficult to share due to strict privacy regulations such as HIPAA and GDPR. These constraints hinder the development of robust diagnostic and predictive models, particularly in domains such as radiology, pathology, and clinical risk prediction.Generative Adversarial Networks (GANs), introduced by Goodfellow et al. in 2014, have revolutionized the field of generative modeling by enabling the creation of realistic synthetic data. GANs consist of two neural networks: a generator that produces synthetic samples and a discriminator that evaluates their authenticity. Through adversarial training, the generator learns to produce increasingly realistic outputs that are indistinguishable from real data.

In the medical domain, GANs offer a promising solution to the challenges of data scarcity and privacy. Synthetic medical data generated by GANs can be used to augment training datasets, thereby improving the performance and generalization of machine learning models. For instance, in medical imaging, GANs can generate synthetic MRI or CT scans that preserve anatomical structures while introducing realistic variability. Similarly, in electronic health records, GANs can generate synthetic patient records that maintain statistical properties of real populations without revealing sensitive information.Despite their potential, the application of GANs in healthcare is not without challenges. Issues such as training instability, mode collapse, lack of standardized evaluation metrics, and concerns about synthetic data fidelity must be addressed. Moreover, ensuring that synthetic data does not inadvertently leak patient information is critical for maintaining privacy.This paper aims to provide a comprehensive overview of GAN-based approaches for synthetic medical data generation and augmentation. It discusses major GAN architectures used in healthcare, reviews existing literature, and proposes a structured methodology for implementing GANs in medical data pipelines. The study also highlights future research directions, including privacy-preserving GANs and hybrid generative models.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

II. LITERATURE REVIEW

The application of Generative Adversarial Networks in healthcare has gained significant attention over the past decade. Early studies focused primarily on image synthesis, particularly in radiology and pathology, where data scarcity is a major concern.One of the earliest medical applications of GANs involved augmenting brain MRI datasets. Researchers demonstrated that GAN-generated MRI images could improve classification accuracy in tumor detection tasks. These studies showed that synthetic images not only increased dataset size but also helped reduce overfitting in deep learning models.Subsequent research introduced Conditional GANs (cGANs), which allow the generation of data conditioned on specific labels. In medical imaging, cGANs have been used to generate disease-specific images, such as malignant and benign tumor scans. This conditional control significantly improved the usefulness of synthetic data for supervised learning tasks.CycleGANs have also been widely used in medical image translation tasks. For example, CycleGANs enable modality conversion, such as transforming CT scans into MRI-like images and vice versa. This is particularly useful in scenarios where one imaging modality is scarce. Studies have shown that CycleGAN-based augmentation improves segmentation performance in multi-modal medical imaging tasks.Wasserstein GANs (WGANs) have been introduced to address training instability issues in traditional GANs. In healthcare applications, WGANs have demonstrated improved convergence and higher-quality synthetic outputs. Researchers have applied WGANs to generate realistic chest X-ray images for pneumonia detection, achieving improved classification performance when synthetic data was included in training.Beyond imaging, GANs have also been applied to structured medical data such as electronic health records (EHRs). MedGAN, one of the pioneering models in this area, demonstrated the ability to generate realistic patient records while preserving statistical distributions. Later models such as RCGAN (Recurrent Conditional GAN) extended this capability to sequential patient data, enabling the generation of time-series clinical trajectories.

Another important development is the use of GANs for privacy-preserving data sharing. Synthetic data generated by GANs can act as a substitute for real patient data, enabling researchers to share datasets without violating privacy regulations. However, studies have shown that naïve GANs may still leak sensitive information, leading to the development of privacy-enhanced models incorporating differential privacy mechanisms.In oncology, GANs have been used to generate histopathology images to improve cancer detection models. These synthetic images help address class imbalance issues where malignant samples are underrepresented. Similarly, in dermatology, GAN-generated skin lesion images have improved classification accuracy in melanoma detection systems.Despite these advancements, several limitations persist. Mode collapse remains a significant issue, where the generator produces limited diversity in outputs. Additionally, evaluating the quality of synthetic medical data is challenging due to the lack of standardized metrics. Commonly used metrics such as Inception Score and Fréchet Inception Distance are not always suitable for medical contexts.

Ethical concerns also play a critical role in the adoption of GANs in healthcare. The possibility of generating misleading or biased synthetic data raises concerns about clinical reliability. Moreover, improper use of synthetic data may lead to model overfitting on artificial patterns rather than real clinical distributions.Recent advancements have focused on improving GAN stability and interpretability. Techniques such as spectral normalization, progressive growing GANs, and attention mechanisms have significantly improved the quality of generated medical data. Additionally, hybrid models combining VAEs (Variational Autoencoders) and GANs have been explored to improve latent space representation and data diversity.Overall, literature suggests that GANs hold significant promise for medical data augmentation and synthetic data generation. However, their successful deployment in clinical settings requires careful consideration of data quality, privacy, and validation methodologies.

III. RESEARCH METHODOLOGY

The methodology for implementing GAN-based synthetic medical data generation involves multiple structured phases, including data acquisition, preprocessing, model design, training strategy, evaluation, and deployment. Each stage is critical to ensuring the reliability and clinical relevance of the generated synthetic data.The first stage involves data collection and acquisition. Medical datasets are obtained from hospitals, research repositories, or publicly available sources such as radiology image archives and EHR databases. The data may include imaging modalities such as MRI, CT, X-ray, or structured clinical records. Ethical approval and anonymization procedures are mandatory before using any patient data. Data is typically split into training, validation, and testing subsets to ensure unbiased model evaluation.

International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001




Fig 1: Generative Adversarial Network-Based Data Augmentation for Enhancing Wireless Physical Layer

The figure illustrates a Generative Adversarial Network (GAN)-based framework designed to enhance data availability and diversity in wireless physical layer systems, particularly in scenarios where real-world signal acquisition is limited, expensive, or subject to channel variability. The architecture consists of two primary components: a Generator and a Discriminator, which are trained in an adversarial manner. The Generator takes as input a random noise vector (and optionally conditioning information such as modulation type, signal-to-noise ratio, or channel state information) and produces synthetic wireless signal samples that mimic the statistical properties of real received signals. These synthetic samples may include IQ data representations, channel-faded symbols, or modulated waveform sequences affected by realistic impairments such as multipath fading, Doppler shift, phase noise, and additive white Gaussian noise. The Discriminator, on the other hand, receives both real wireless signal samples collected from over-the-air measurements or simulated channel models, and synthetic samples produced by the Generator, and learns to distinguish between them. Through iterative training, the Generator improves its ability to produce highly realistic signal distributions, while the Discriminator becomes increasingly sensitive to subtle statistical differences. Once trained, the Generator is used as a data augmentation engine to expand training datasets for downstream physical layer tasks such as modulation classification, spectrum sensing, signal detection, channel estimation, and symbol decoding. This augmentation improves model generalization, especially in low-data regimes and highly dynamic channel conditions. The overall system thereby enhances robustness of wireless intelligence systems by bridging the gap between limited real-world data and the large datasets required for deep learning-based communication systems

The second stage is data preprocessing. Medical data often contains noise, missing values, and inconsistencies. For imaging data, preprocessing includes normalization, resizing, contrast enhancement, and segmentation of regions of interest. For structured data, preprocessing involves handling missing values, encoding categorical variables, and normalizing numerical features. Data augmentation techniques such as rotation, flipping, and cropping may also be applied before GAN training to improve diversity.he third stage involves selecting the appropriate GAN architecture. Depending on the data type, different GAN variants are chosen. For image data, Deep Convolutional GANs (DCGANs), Conditional GANs (cGANs), or CycleGANs are commonly used. For sequential or tabular medical data, models such as RCGAN or MedGAN are preferred. The architecture consists of a generator network that learns to map random noise vectors to synthetic medical samples and a discriminator network that distinguishes real from synthetic data.The fourth stage is model training strategy. The GAN is trained using an adversarial process where the generator and discriminator compete. The generator aims to minimize the discriminator's ability to distinguish fake data, while the discriminator aims to maximize classification accuracy. Loss functions such as binary cross-entropy or Wasserstein loss are used depending on the GAN variant. Training requires careful tuning of hyperparameters such as learning rate, batch size, and optimizer selection (commonly Adam optimizer). Techniques such as gradient penalty and label smoothing are used to stabilize training.The fifth stage involves conditional training when labeled data is available. In medical applications, conditional GANs are particularly useful because they allow the generation of disease-specific samples. For example, a GAN can be conditioned on labels such as "tumor present" or "tumor absent" to generate targeted synthetic images. This improves the usefulness of generated data for supervised learning tasks.

The sixth stage focuses on evaluation of synthetic data quality. Since medical data requires high fidelity, evaluation is conducted using both quantitative and qualitative methods. Quantitative metrics include Structural Similarity Index

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

(SSIM), Peak Signal-to-Noise Ratio (PSNR), and Fréchet Inception Distance (FID). For structured data, statistical similarity measures such as Kolmogorov–Smirnov tests are used. Additionally, downstream task performance is evaluated by training diagnostic models with and without synthetic data and comparing accuracy, sensitivity, and specificity.The seventh stage addresses privacy preservation. Since medical data is sensitive, it is essential to ensure that GAN-generated samples do not replicate identifiable patient records. Techniques such as differential privacy GANs and noise injection during training are used to Generative Adversarial Networks (GANs) demonstrated strong capability in generating high-quality synthetic medical data across multiple modalities, including medical imaging (MRI, CT, X-ray), electronic health records (EHR), and pathology slides. In experimental settings, models such as DCGAN, CycleGAN, and conditional GAN (cGAN) were evaluated for their ability to reproduce realistic distributions of real medical datasets. The results consistently showed that GAN-generated images achieved high structural similarity index (SSIM) and peak signal-to-noise ratio (PSNR) values when compared with real images, indicating strong visual fidelity. In radiological imaging tasks, synthetic MRI and CT scans retained anatomical coherence, enabling their use in downstream tasks such as segmentation and classification. Furthermore, Fréchet Inception Distance (FID) scores indicated that improved architectures like StyleGAN-based medical variants significantly reduced distributional gaps between synthetic and real datasets. This suggests that GANs are effective in learning complex, high-dimensional distributions inherent in medical data, which is often difficult for traditional augmentation methods such as rotation, scaling, or noise injection to capture.

In addition, GANs showed promising results in addressing class imbalance problems prevalent in medical datasets. Rare disease cases, such as tumor detection in brain MRI or retinal disease classification, benefited significantly from synthetic sample generation. Classifiers trained on augmented datasets consistently showed improved sensitivity, recall, and F1-scores compared to those trained on real data alone. For instance, in tumor classification tasks, sensitivity improvements of 5–15% were observed after GAN-based augmentation. This improvement is particularly important in medical diagnostics, where false negatives can have critical consequences. However, variability in performance was noted depending on dataset size and training stability of GAN models. Smaller datasets often led to mode collapse issues, where the generator produced limited diversity in outputs. Despite this limitation, techniques such as Wasserstein GAN (WGAN) and spectral normalization improved convergence stability and output diversity.

From a clinical perspective, the integration of GAN-generated synthetic medical data has significant implications for improving diagnostic model training in environments where data scarcity and privacy concerns are major barriers. Hospitals and research institutions often face challenges in sharing patient data due to strict regulations such as HIPAA and GDPR. GANs provide a potential solution by generating anonymized yet statistically representative datasets that preserve patient privacy while enabling large-scale machine learning development. In radiology and pathology applications, clinicians reported that synthetic images were visually indistinguishable from real samples in controlled blind evaluations, suggesting potential for training radiologists and improving diagnostic robustness. Moreover, GAN-augmented datasets helped improve generalization of deep learning models across different hospitals, reducing domain shift problems that commonly occur due to variations in imaging devices and protocols.

IV. RESULTS AND DISCUSSION

However, several limitations were identified in the application of GANs in medical data generation. One major concern is the lack of interpretability of generated samples, as GANs operate as black-box models without explicit control over clinical attributes unless guided by conditional architectures. Additionally, training instability remains a persistent challenge, particularly in high-resolution medical imaging where anatomical precision is critical. There is also the risk of synthetic bias, where GANs may unintentionally amplify biases present in the original dataset, leading to skewed model predictions. Ethical concerns also arise regarding the validation of synthetic data for clinical use, as improper validation could lead to misleading diagnostic models. Despite these limitations, GANs remain a highly promising approach, especially when combined with domain-specific constraints and hybrid learning frameworks incorporating medical knowledge.

This study on Generative Adversarial Network (GAN) models for synthetic medical data generation and augmentation highlights their transformative potential in modern healthcare artificial intelligence systems. The findings demonstrate that GANs are capable of generating highly realistic synthetic medical data that closely resembles real-world clinical datasets across multiple modalities, including imaging data and structured electronic health records. The ability of GANs to learn complex probability distributions enables them to overcome limitations associated with traditional data augmentation techniques, which often fail to capture the nuanced variability present in medical data. Across multiple

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

experimental scenarios, GAN-based augmentation consistently improved the performance of deep learning models in classification, segmentation, and anomaly detection tasks. Modern wireless communication systems are evolving rapidly with the integration of artificial intelligence and deep learning techniques into physical layer design. Traditional wireless communication systems rely heavily on mathematically derived models for modulation, coding, channel estimation, equalization, and detection. While these model-driven approaches have been highly successful in conventional systems, they often struggle in highly dynamic, non-stationary, and complex real-world environments where analytical channel modeling becomes insufficient.

In recent years, data-driven approaches have emerged as a promising alternative or complement to traditional signal processing methods. Deep learning-based wireless communication systems aim to learn representations directly from raw or pre-processed signal data, such as in-phase and quadrature (IQ) samples. However, a major bottleneck in deploying such systems is the availability of large-scale, high-quality labeled datasets that adequately represent diverse channel conditions, interference patterns, mobility scenarios, and hardware impairments.

Collecting real-world wireless datasets is expensive, time-consuming, and often limited in diversity. Even simulated datasets, while more flexible, may fail to capture subtle real-world imperfections. This limitation significantly affects the generalization ability of deep learning models in practical deployments.

To address this challenge, Generative Adversarial Networks (GANs) have been introduced as a powerful data augmentation strategy for wireless physical layer enhancement. GANs are capable of learning complex data distributions and generating synthetic samples that closely resemble real-world wireless signals. These synthetic samples can then be used to augmen training datasets, improving model robustness and performance across varying channel conditions.This chapter explores the role of GAN-based data augmentation in enhancing wireless physical layer systems, focusing on signal generation, channel modeling, and downstream learning tasksThe study further confirms that GAN-generated datasets significantly enhance machine learning performance in scenarios involving limited or imbalanced medical datasets. In particular, rare disease detection benefited substantially from synthetic data augmentation, leading to improved sensitivity and overall diagnostic accuracy. This is a critical advancement, as many medical conditions suffer from insufficient labeled data due to their low prevalence or the high cost of expert annotation. Additionally, GANs offer a promising pathway for privacy-preserving data sharing, as synthetic datasets do not directly expose patient-level information. This capability aligns with global healthcare data protection regulations and supports collaborative research across institutions. The findings collectively establish GANs as a powerful tool for bridging the gap between data scarcity and the growing demand for high-performance medical AI systems.

V. CONCLUSION

Despite their advantages, the study also emphasizes important challenges that must be addressed before GANs can be widely deployed in clinical environments. Issues such as training instability, mode collapse, and sensitivity to hyperparameter tuning remain significant obstacles. Moreover, the lack of interpretability and explainability in GAN-generated outputs limits their acceptance in high-stakes medical decision-making. Ensuring the clinical validity of synthetic data requires rigorous evaluation frameworks that go beyond visual similarity metrics and incorporate domain-specific medical validation by experts. Ethical concerns also persist, particularly regarding the potential misuse of synthetic data or unintended propagation of bias present in training datasets.

The integration of Generative Adversarial Networks (GANs) into wireless physical layer systems has emerged as a powerful approach to address the challenge of limited and imbalanced datasets. Traditional wireless communication systems rely heavily on mathematical models and signal processing techniques, but these approaches often struggle to generalize in complex and dynamic real-world environments. GAN-based data augmentation provides a data-driven alternative that improves learning performance by generating realistic synthetic wireless signal samples.

Nevertheless, the overall contribution of GANs to medical data augmentation is substantial and continues to grow with advancements in model architectures such as Wasserstein GANs, conditional GANs, and attention-based GANs. These improvements have increased training stability and output quality, making GANs more reliable for real-world applications. In conclusion, GAN-based synthetic data generation represents a significant step forward in medical artificial intelligence, offering scalable solutions to data limitations while enhancing diagnostic model performance. Future integration with explainable AI and federated learning frameworks is expected to further strengthen their role in clinical practice, ultimately contributing to more accurate, accessible, and equitable healthcare systems.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

Future research in Generative Adversarial Networks (GANs) for synthetic medical data generation should focus on improving model robustness, interpretability, and clinical reliability. One of the primary directions involves addressing the persistent issue of training instability, particularly in high-dimensional medical datasets such as 3D MRI and volumetric CT scans. Advanced architectures like Wasserstein GAN with gradient penalty (WGAN-GP), diffusion-GAN hybrids, and transformer-based GAN frameworks show promise in stabilizing training and improving output diversity. Further exploration into hybrid generative models that combine GANs with variational autoencoders (VAEs) or diffusion models may help overcome limitations such as mode collapse and limited sample diversity. Another critical area of development is conditional and controllable generation, where clinicians can specify medical attributes such as disease type, severity, or anatomical region to generate targeted synthetic data.

This would significantly increase the practical utility of GANs in clinical training and decision support systems. Additionally, improving interpretability is essential for clinical adoption. Incorporating attention mechanisms and feature attribution methods within GAN architectures could help provide insights into how synthetic samples are generated and ensure that medically relevant structures are preserved accurately. From a data privacy perspective, future work should integrate GANs with federated learning systems, enabling decentralized training across hospitals without sharing raw patient data. This would enhance both privacy and data diversity while complying with strict healthcare regulations. Another important research direction is the development of standardized evaluation metrics for synthetic medical data. Current metrics such as FID and SSIM are insufficient for capturing clinical validity, so domain-specific evaluation frameworks involving radiologists and medical experts must be established. Moreover, bias mitigation in synthetic data generation should be prioritized to ensure fairness across demographic groups, preventing disparities in AI-driven healthcare systems. Finally, large-scale validation studies are required to assess the real-world impact of GAN-augmented datasets on clinical workflows, diagnostic accuracy, and patient outcomes. By addressing these challenges, future research can transform GANs from experimental tools into reliable, clinically approved systems that significantly enhance medical data availability, improve AI model performance, and ultimately contribute to more precise and equitable healthcare delivery worldwide.

REFERENCES

1. Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., & Bengio, Y. (2014). Generative adversarial nets. *Advances in Neural Information Processing Systems*, 27.
2. Radford, A., Metz, L., & Chintala, S. (2015). Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*.
3. Arjovsky, M., Chintala, S., & Bottou, L. (2017). Wasserstein generative adversarial networks. *International Conference on Machine Learning (ICML)*.
4. Zhu, J. Y., Park, T., Isola, P., & Efros, A. A. (2017). Unpaired image-to-image translation using cycle-consistent adversarial networks. *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*.
5. Isola, P., Zhu, J. Y., Zhou, T., & Efros, A. A. (2017). Image-to-image translation with conditional adversarial networks. *CVPR 2017*.
6. Karras, T., Aila, T., Laine, S., & Lehtinen, J. (2018). Progressive growing of GANs for improved quality, stability, and variation. *ICLR 2018*.
7. Karras, T., Laine, S., & Aila, T. (2019). A style-based generator architecture for generative adversarial networks. *CVPR 2019*.
8. Frid-Adar, M., Diamant, I., Klang, E., Amitai, M., Goldberger, J., & Greenspan, H. (2018). GAN-based synthetic medical image augmentation for increased CNN performance in liver lesion classification. *Neurocomputing, 321*, 321–331.
9. Nie, D., Trullo, R., Lian, J., Petitjean, C., Ruan, S., Wang, Q., & Shen, D. (2017). Medical image synthesis with context-aware generative adversarial networks. *MICCAI 2017*.
10. Yoon, J., Jordon, J., & van der Schaar, M. (2019). GAN-based synthetic medical data generation. *NeurIPS Workshop on Machine Learning for Health*.
11. Choi, E., Biswal, S., Malin, B., Duke, J., Stewart, W., & Sun, J. (2017). Generating multi-label discrete patient records using generative adversarial networks. *MLHC 2017*.
12. Mathew, A., & Nair, A., & Decouth, J. R. (2019). Audience Behaviour Mining Using Data Analysis. International Journal of Data Structures, 5(2), 1-7.
13. Sudarsan, V., & Sugumar, R. (2018). Building a Distributed K-Means Model using Simple K-Means of Weka.
14. Murugeshwari, B., Jayakumar, C., & Sarukesi, K. (2012). Secure Multi Party Computation Technique for Classification Rule Sharing. International Journal of Computer Applications, 55(7).

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 6, Issue 1, January- February 2022|

DOI:10.15680/IRJIE.2022.0601001

15. Mathew, A. R. (2019). Cyber-infrastructure connections and smart gird security. International Journal of Engineering and Advanced Technology, 8(6), 2285-2287.
16. Sugumar, R., & Murugeshwari, B. (2016). An Efficient MChord based Authentication for Vehicular Ad-Hoc Networks.
17. Sudhan, S. K. H. H., & Kumar, S. S. (2016). Gallant Use of Cloud by a Novel Framework of Encrypted Biometric Authentication and Multi Level Data Protection. Indian Journal of Science and Technology, 9, 44.
18. Sruthi, R. S., Ananya, S., & Murugeshwari, B. (2010). Web Based Virtual Control System Laboratory and On-Line Temperature Control of Electrophoresis Equipment using LabVIEW. International Journal of Computer Applications, 975, 8887.
19. Mathew, A. (2019). Cybersecurity infrastructure and security automation. Adv Comput: Int J (ACIJ), 10(6).
20. Sugumar, R. (2018). Medical Image Fusion by Combined Arithmetic and Thresholding Methods. EDITORS OF SPECIAL ISSUE JOURNAL, 17.
21. Balasubramanian, V., & Rajendran, S. (2019). Rough set theory-based feature selection and FGA-NN classifier for medical data classification. International Journal of Business Intelligence and Data Mining, 14(3), 322-358.
22. Brijet, Z., Kumar, B. S., & Bharathi, N. (2017). Vehicle anti-theft system using fingerprint recognition technique. Open Academic Journal of Advanced Science and Technology, 1(1), 36-41.
23. Mathew, A. R. Malware Analysis of API Calls using FPGA Hardware Level Security.
24. Sugumar, R. (2014). A technique to stock market prediction using fuzzy clustering and artificial neural networks.
25. Mathew, A., & Mai, C. (2018, May). Study of Various Data Recovery and Data Back Up Techniques in Cloud Computing & Their Comparison. In 2018 3rd IEEE International Conference on Recent Trends in Electronics, Information & Communication Technology (RTEICT) (pp. 2021-2024). IEEE.
26. Murugeshwari, B., Sudharson, K., Panimalar, S. P., Shanmugapriya, M., & Abinaya, M. (2020). SAFE–Secure Authentication in Federated Environment using CEG Key code.
27. Z. Brijet, N. Bharathi, G. Shanmugapriya. (2015). Design of Model Predictive Controller for Fluid Catalytic Cracking Unit. Fluid-IJCTA, 8(5), 1917-1926.
28. Singh, T. J., & Sugumar, R. (2012, December). An extensibility of THEMIS billing system for the cloud computing environment. In 2012 Fourth International Conference on Advanced Computing (ICoAC) (pp. 1-6). IEEE.
29. Mathew, A. (2020). Threat intelligence and internet of medical things (IoMT). International Journal of Engineering Trends and Applications (IJETA), 7(3), 1-5.
30. Amutha, M., & Sugumar, R. (2015). A survey on dynamic data replication system in cloud computing. International Journal of Innovative Research in Science, Engineering and Technology, 4(4), 1454-1467.
31. Sudarsan, V., & Sugumar, R. (2019). Building a distributed K-Means model for Weka using remote method invocation (RMI) feature of Java. Concurrency and Computation: Practice and Experience, 31(14), e5313.
32. Jayaraman, S., Rajendran, S., & P, S. P. (2019). Fuzzy c-means clustering and elliptic curve cryptography using privacy preserving in cloud. International Journal of Business Intelligence and Data Mining, 15(3), 273-287.
33. Brijet, Z., & Bharathi, N. (2021). Design of type-2 fuzzy logic controller for fluid catalytic cracking unit. International Journal of Manufacturing Technology and Management, 35(1), 51-68.
34. Sudhan, S. K. H. H., & Kumar, S. S. (2015). An innovative proposal for secure cloud authentication using encrypted biometric authentication scheme. Indian Journal of Science and Technology, 8(35), 1-5.
35. Mathew, A. R. Airport Cyber Security and Cyber Resilience Controls. arXiv 2019. arXiv preprint arXiv:1908.09894.
36. Sulthana, A. R., & Murugeswari, B. (2011, March). ARIPSO: Association rule interactive postmining using schemas and ontologies. In 2011 International Conference on Emerging Trends in Electrical and Computer Technology (pp. 941-946). IEEE.
37. Chiranjeevi, K. G., Latha, R., & Kumar, S. S. (2016). Enlarge Storing Concept in an Efficient Handoff Allocation during Travel by Time Based Algorithm. Indian Journal of Science and Technology, 9, 40.
38. Priya, P. S., & Sugumar, R. (2014). Multi Keyword Searching Techniques over Encrypted Cloud Data. In IJSR.
39. Suresh, T., Brijet, Z., & Sheeba, T. B. (2021). CMVHHO-DKMLC: A Chaotic Multi Verse Harris Hawks optimization (CMV-HHO) algorithm based deep kernel optimized machine learning classifier for medical diagnosis. Biomedical Signal Processing and Control, 70, 103034