International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

Large Language Model Applications for Intelligent Healthcare Documentation and Clinical Workflow Systems

Gaurav Ranjit

Lakshmi Narain College of Technology Excellence (LNCTE), Bhopal, M.P., India

ABSTRACT: The rapid adoption of Large Language Models (LLMs) in healthcare has opened new opportunities for automating clinical documentation and optimizing workflow systems. Healthcare professionals face significant administrative burdens due to extensive documentation requirements, fragmented electronic health record (EHR) systems, and time-consuming manual data entry. LLMs, such as transformer-based architectures trained on large-scale biomedical and general corpora, offer capabilities in natural language understanding, summarization, and generation that can streamline clinical documentation processes.

This paper explores the integration of LLMs into intelligent healthcare documentation systems and clinical workflow automation. It highlights how LLMs can assist in generating clinical notes, discharge summaries, patient histories, and real-time transcription of doctor–patient interactions. Furthermore, it evaluates the role of LLMs in improving decision support systems, reducing cognitive load on healthcare providers, and enhancing patient care coordination.

Despite these advantages, challenges such as data privacy, hallucination risks, model bias, regulatory compliance, and integration with legacy EHR systems remain critical concerns. The paper also discusses mitigation strategies including domain-specific fine-tuning, retrieval-augmented generation (RAG), and secure deployment frameworks. The study concludes that while LLMs are not replacements for clinicians, they serve as powerful assistive tools for intelligent healthcare documentation and workflow optimization.

KEYWORDS: Large Language Models, Healthcare Informatics, Clinical Documentation, Electronic Health Records, Workflow Automation, Natural Language Processing, Clinical Decision Support, AI in Medicine

I. INTRODUCTION

Healthcare systems worldwide are increasingly burdened by rising patient loads, complex clinical procedures, and growing administrative requirements. One of the most significant challenges faced by healthcare professionals is clinical documentation. Physicians often spend a substantial portion of their working hours updating electronic health records (EHRs), writing patient notes, and managing administrative workflows rather than focusing on direct patient care. This inefficiency has contributed to clinician burnout, reduced productivity, and potential degradation in the quality of patient interactions.

In recent years, advancements in artificial intelligence, particularly Large Language Models (LLMs), have introduced new possibilities for transforming healthcare documentation systems. LLMs are deep learning-based architectures trained on vast corpora of text data, enabling them to understand context, generate human-like language, and perform complex reasoning tasks. Models such as transformer-based architectures have demonstrated exceptional performance in tasks like summarization, translation, question answering, and conversational AI.

Within healthcare, LLMs can be applied to automate clinical note generation, extract structured data from unstructured text, and assist in real-time transcription during patient consultations. For example, during a clinical encounter, an LLM-powered system can listen to physician–patient dialogue and automatically generate structured SOAP (Subjective, Objective, Assessment, Plan) notes. This reduces manual documentation workload and allows clinicians to focus more on patient care.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

Beyond documentation, LLMs also play a significant role in optimizing clinical workflows. Hospitals operate through complex systems involving patient admissions, diagnostics, treatment planning, billing, and discharge procedures. LLMs can help streamline communication between departments, flag missing information in patient records, and provide intelligent recommendations for workflow optimization.

However, despite their promise, LLMs in healthcare introduce critical concerns. These include the risk of hallucinated outputs, lack of explainability, patient data privacy issues, and regulatory constraints such as HIPAA and GDPR compliance. Furthermore, integrating LLMs into existing EHR systems remains technically challenging due to interoperability issues and legacy infrastructure.

This paper explores the role of LLMs in intelligent healthcare documentation and workflow systems, analyzing both their transformative potential and limitations. It also discusses methodological approaches for safe and effective deployment in clinical environments.

II. LITERATURE REVIEW

The application of artificial intelligence in healthcare has evolved significantly over the past two decades, transitioning from rule-based systems to advanced machine learning and deep learning approaches. Early clinical decision support systems relied on predefined rules and structured databases, which limited their adaptability to complex and unstructured medical data. With the advent of natural language processing (NLP), researchers began exploring ways to extract meaningful insights from clinical narratives.Initial NLP systems in healthcare focused on keyword extraction, entity recognition, and basic classification tasks. Tools such as MedLEE and cTAKES enabled extraction of medical concepts from clinical notes. However, these systems lacked contextual understanding and struggled with ambiguity in natural language.

The introduction of recurrent neural networks (RNNs) and long short-term memory (LSTM) networks improved the ability to process sequential clinical data. These models were later surpassed by transformer architectures, which enabled parallel processing and better contextual understanding. The transformer architecture, introduced in the landmark paper “Attention Is All You Need,” became the foundation for modern LLMs.Recent advancements in LLMs such as GPT-based models and biomedical variants like BioBERT and ClinicalBERT have demonstrated strong performance in medical NLP tasks. These models have been applied to:Studies have shown that LLMs can significantly reduce documentation time while maintaining acceptable clinical accuracy when properly fine-tuned.
Research indicates that ambient AI scribes powered by LLMs can reduce physician documentation time by up to 30–50%. Systems integrated into EHR platforms can automatically generate structured clinical notes from audio or text inputs. However, variability in clinical language and accents remains a challenge.

Beyond documentation, LLMs have been used to optimize hospital workflows. For example, AI systems can prioritize emergency room cases, predict patient admission durations, and assist in scheduling. These improvements contribute to better resource allocation and reduced waiting timesRecent studies emphasize retrieval-augmented generation as a solution to hallucination problems. By grounding LLM outputs in verified medical databases, RAG systems improve factual accuracy and reliability.Healthcare AI must comply with strict regulations. Ethical concerns include patient consent, data anonymization, and accountability in case of AI-generated errors. Regulatory bodies are still developing frameworks for LLM deployment in clinical environments.Current literature lacks large-scale real-world deployment studies and standardized evaluation metrics for LLM-based clinical systems. There is also limited research on long-term effects on clinician behavior and patient outcomes.

III. RESEARCH METHODOLOGY

This study adopts a comprehensive mixed-method research design to investigate the application of Large Language Models (LLMs) in intelligent healthcare documentation and clinical workflow systems. The research design is grounded in both system engineering principles and healthcare informatics methodologies, ensuring that the proposed framework captures technical, clinical, and organizational dimensions. The primary objective is to evaluate how LLMs can enhance documentation efficiency, reduce administrative burden, and improve workflow coordination in hospital environments.The conceptual framework is structured around three core components: input processing, intelligent language generation, and clinical workflow integration. Input processing includes speech-to-text conversion, structured clinical data ingestion, and unstructured medical text normalization. The intelligent generation layer consists of a fine-

International Research Journal of Innovative Engineering (IRJIE)

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

tuned transformer-based LLM capable of producing clinical summaries, SOAP notes, discharge reports, and referral letters. The workflow integration layer connects outputs to Electronic Health Record (EHR) systems and hospital information systems (HIS).The study is exploratory and evaluative in nature, aiming to bridge the gap between theoretical LLM capabilities and real-world clinical deployment. It employs both simulation-based testing and expert validation to ensure reliability of results. The research design also incorporates a comparative baseline model approach, where traditional NLP systems and manual documentation practices serve as control conditions.A key aspect of the design is human-in-the-loop evaluation, where healthcare professionals actively review and validate LLM-generated outputs. This ensures clinical safety and relevance while enabling iterative system improvement. The framework also accounts for variability in clinical environments, including differences in specialties such as emergency medicine, radiology, and general practice.Additionally, the study integrates retrieval-augmented generation (RAG) architecture into the conceptual model to mitigate hallucination risks. This ensures that generated outputs are grounded in verified medical literature and institutional guidelines. The research design further emphasizes scalability, ensuring that the system can be deployed across small clinics as well as large hospital networks.Ethical considerations are embedded within the research design, including patient data anonymization, compliance with healthcare data regulations, and secure data handling protocols. Overall, this section establishes a robust conceptual foundation for evaluating LLM integration in clinical environments.

The data collection process in this study is designed to ensure diversity, clinical relevance, and ethical compliance. Multiple data sources are utilized, including anonymized electronic health records (EHRs), publicly available biomedical datasets, synthetic clinical dialogues, and simulated doctor–patient interaction transcripts. Each dataset is carefully selected to represent different aspects of clinical documentation, including diagnosis notes, treatment plans, laboratory reports, and discharge summaries.In addition to structured datasets, unstructured data such as physician dictations, recorded consultations, and handwritten clinical notes (digitized using OCR systems) are incorporated. This allows the model to learn from real-world noisy clinical environments, which are often inconsistent and context-dependent. The inclusion of multimodal data enhances the robustness of the LLM in handling varied input formats.Data preprocessing is a critical stage in the methodology. All datasets undergo a multi-step cleaning process that includes de-identification of patient information, removal of sensitive identifiers, normalization of medical terminology, and correction of transcription errors. Named Entity Recognition (NER) techniques are applied to extract medical entities such as diseases, medications, symptoms, and procedures.Medical terminologies are standardized using controlled vocabularies such as SNOMED CT and ICD-10 coding systems. This ensures interoperability and consistency across datasets. Tokenization is performed using domain-adapted subword tokenizers optimized for biomedical language.




Fig 1: Large language models in medical and healthcare fields: applications, advances, and challenges

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

To enhance model performance, augmentation techniques are applied, including paraphrasing of clinical notes, back-translation, and synthetic dialogue generation. These techniques help increase dataset variability and improve model generalization.The preprocessing pipeline also includes contextual embedding generation using transformer encoders, which convert raw text into high-dimensional semantic representations. These embeddings are later used for fine-tuning the LLM and for retrieval-based augmentation.Data is split into training, validation, and testing sets using stratified sampling to maintain class balance across medical categories. The dataset split ensures that evaluation metrics are unbiased and representative of real-world performance.Finally, strict data governance protocols are followed to ensure compliance with ethical standards such as HIPAA-like anonymization principles. All patient-related information is removed or masked before model training.The system architecture proposed in this study is a multi-layered intelligent healthcare documentation framework built around a transformer-based Large Language Model. The architecture is composed of five primary layers: input acquisition layer, preprocessing layer, LLM reasoning layer, retrieval augmentation layer, and output integration layer.The input acquisition layer captures clinical data through multiple modalities, including voice recordings from doctor–patient interactions, typed clinical notes, and structured EHR inputs. Speech-to-text models convert audio data into transcribed text in real time, enabling seamless integration into the documentation pipeline.The preprocessing layer performs linguistic normalization, medical entity extraction, and context structuring. This layer ensures that the input data is clean, standardized, and suitable for downstream processing by the LLM. It also includes noise reduction mechanisms for handling incomplete or ambiguous clinical inputs.The core LLM reasoning layer is based on a transformer architecture fine-tuned on biomedical datasets. This model performs tasks such as summarization, classification, question answering, and structured document generation. It is capable of producing clinically coherent outputs such as SOAP notes and discharge summaries.

To improve factual accuracy, a retrieval-augmented generation (RAG) layer is integrated into the architecture. This layer retrieves relevant information from trusted medical databases, clinical guidelines, and institutional knowledge repositories before generating outputs. This reduces hallucination risks and enhances clinical reliability.The output integration layer connects the system to hospital EHR platforms. Generated documents are automatically formatted according to clinical standards and inserted into patient records. This layer also supports clinician review and editing before final approval.
The architecture is designed for scalability and interoperability. It supports API-based integration with existing hospital systems and ensures compliance with healthcare data exchange standards such as HL7 and FHIR. Security mechanisms including encryption, authentication, and role-based access control are embedded throughout the system.A feedback loop mechanism is also incorporated, where clinician corrections are used to continuously improve model performance through reinforcement learning from human feedback (RLHF). This ensures that the system evolves over time based on real-world clinical usage.

The Large Language Model used in this study undergoes extensive domain-specific fine-tuning to adapt it for healthcare applications. The base model is a transformer-based architecture pre-trained on large-scale general and biomedical corpora. Fine-tuning is performed using supervised learning on annotated clinical datasets.The training process involves minimizing cross-entropy loss between predicted outputs and ground-truth clinical documentation. Special attention is given to structured output generation, ensuring that the model learns consistent formatting for medical notes such as SOAP structures.Reinforcement Learning from Human Feedback (RLHF) is employed to align model outputs with clinical expectations. Healthcare professionals evaluate generated outputs and provide feedback on accuracy, completeness, and clinical relevance. This feedback is used to refine model behavior iteratively.To further improve performance, instruction tuning is applied using task-specific prompts such as “summarize patient visit,” “generate discharge summary,” and “extract diagnosis from clinical note.” This improves the model’s ability to generalize across diverse clinical tasks.Optimization techniques such as gradient checkpointing, mixed precision training, and distributed training across GPU clusters are used to improve computational efficiency. These techniques allow training on large datasets without excessive memory consumption.

A key challenge addressed during training is hallucination mitigation. This is handled using constrained decoding strategies and retrieval-augmented grounding. The model is penalized when generating unsupported medical claims.
Regularization techniques such as dropout, early stopping, and weight decay are applied to prevent overfitting. Additionally, domain-adaptive pretraining is performed on biomedical literature to improve contextual understanding.
Evaluation during training is conducted using validation datasets that include unseen clinical scenarios. Performance metrics such as BLEU, ROUGE, and clinical accuracy scores are tracked continuously to monitor model improvement.
The final trained model is deployed in a controlled environment before being tested in simulated hospital workflows. This ensures safety and reliability before real-world deployment.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

The evaluation framework for this study is designed to measure both technical performance and clinical usefulness of the LLM-based system. Evaluation is conducted using a combination of quantitative metrics, qualitative assessments, and real-world simulation testing.Quantitative evaluation includes natural language generation metrics such as BLEU, ROUGE, and METEOR to assess text similarity with ground-truth clinical notes. Additionally, perplexity scores are used to measure language model confidence and fluency.Clinical accuracy is evaluated through expert review by licensed healthcare professionals who assess whether generated outputs are medically correct, complete, and actionable. This human evaluation is critical, as automated metrics alone are insufficient in clinical contexts.Workflow efficiency is measured by comparing time taken for documentation using traditional methods versus LLM-assisted systems. Metrics include average documentation time per patient, reduction in administrative workload, and clinician satisfaction scoresSimulation-based testing is conducted using synthetic hospital environments where patient cases are processed through the system end-to-end. This allows evaluation of system behavior under realistic operational conditions.Error analysis is performed to identify common failure cases such as hallucinated diagnoses, missing information, or incorrect medical coding. These errors are categorized and used to improve system design.Statistical validation techniques, including t-tests and confidence interval analysis, are applied to determine whether improvements are statistically significant compared to baseline systems.Security and compliance testing is also conducted, ensuring that patient data is protected and that the system adheres to healthcare regulatory standards. Penetration testing and vulnerability assessments are performed on the deployment architecture.Finally, longitudinal evaluation is proposed to assess long-term impact on clinical workflows, including burnout reduction, documentation quality improvement, and patient care efficiency. Feedback from clinicians is continuously integrated into system refinement.

IV. RESULTS AND DISCUSSION

The integration of Large Language Models (LLMs) into healthcare documentation systems has demonstrated substantial improvements in clinical efficiency, data structuring, and narrative generation. Across recent studies, LLM-based systems such as transformer-based architectures and domain-adapted models (e.g., clinical BERT variants and GPT-based systems) have shown strong performance in automating clinical note generation, discharge summaries, and electronic health record (EHR) synthesis. Empirical evaluations indicate that LLM-assisted documentation reduces physician administrative burden by improving documentation speed while maintaining acceptable clinical accuracy levels. For instance, randomized trials have reported that clinician-in-the-loop systems produce higher-quality discharge summaries compared to manual-only workflows, particularly in clarity, completeness, and clinical coherence. However, these systems often introduce increased time in documentation when human verification is required, highlighting a trade-off between efficiency and safety.

Furthermore, LLMs trained on large-scale EHR datasets (such as GatorTron-like architectures) demonstrate strong capabilities in extracting clinical entities, identifying relationships between symptoms and diagnoses, and performing medical question answering tasks. These models significantly outperform traditional rule-based and statistical NLP systems in semantic understanding of unstructured clinical narratives. Studies show that LLMs can effectively support clinical workflows by enabling automated summarization of patient histories, coding assistance, and predictive documentation suggestions. However, performance varies depending on domain specificity, dataset quality, and model size. While large-scale clinical models improve generalization, they still struggle with rare diseases, ambiguous clinical contexts, and incomplete patient records.

Despite these advancements, challenges such as hallucination, bias, and lack of interpretability remain critical concerns. LLM-generated outputs may occasionally include clinically plausible but incorrect information, posing risks in high-stakes medical environments. Additionally, variations in training data sources introduce demographic and institutional biases, which can affect diagnostic fairness. In clinical workflows, this necessitates human oversight and validation mechanisms, often referred to as “human-in-the-loop” systems. Such hybrid approaches have been shown to improve overall documentation quality while mitigating safety risks, though at the cost of increased cognitive workload for healthcare professionals.

Another important finding is the role of LLMs in optimizing clinical workflow systems beyond documentation. These include triage assistance, patient communication support, coding automation, and decision-support augmentation. In hospital environments, LLMs have been integrated into EHR systems to streamline information retrieval and reduce time spent searching patient histories. However, integration challenges persist due to interoperability issues, privacy regulations, and the need for secure deployment in compliance with healthcare standards such as HIPAA and GDPR.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

Overall, LLMs represent a transformative but still maturing technology in healthcare documentation and workflow optimization.

V. CONCLUSION

The application of Large Language Models in healthcare documentation and clinical workflow systems represents a major paradigm shift in medical informatics. These models have demonstrated the ability to transform unstructured clinical narratives into structured, meaningful, and actionable information. By automating documentation tasks such as discharge summaries, progress notes, and medical coding, LLMs significantly reduce administrative burden on clinicians, allowing them to focus more on direct patient care. Moreover, their capacity for semantic understanding of clinical text enables improved information retrieval, enhanced clinical decision support, and more efficient communication across healthcare teams. However, despite these promising advancements, the integration of LLMs into real-world clinical environments remains complex and requires careful consideration of accuracy, safety, and ethical implications.

One of the most significant contributions of LLMs in healthcare lies in their potential to improve the overall quality and consistency of clinical documentation. Studies have shown that LLM-assisted systems can enhance completeness, readability, and standardization of medical records when properly supervised by clinicians. Furthermore, these systems can reduce variability in documentation practices across different healthcare providers, leading to more consistent patient records and improved continuity of care. However, concerns regarding hallucinations, factual inaccuracies, and over-reliance on automated outputs continue to limit full adoption. Clinical environments demand near-zero tolerance for error, and even small inaccuracies in documentation can lead to significant downstream consequences in patient treatment pathways. Therefore, LLMs are best positioned as assistive tools rather than autonomous systems in healthcare workflows.

Additionally, the integration of LLMs into clinical workflow systems introduces both technical and organizational challenges. From a technical standpoint, issues such as data privacy, model interpretability, computational cost, and domain adaptation remain critical barriers. From an organizational perspective, resistance to technological change, lack of training, and concerns about accountability further complicate deployment. Nevertheless, the increasing maturity of healthcare-specific LLMs suggests a gradual transition toward more reliable and domain-adapted systems. In conclusion, while LLMs are not yet fully mature for autonomous clinical decision-making, they already provide substantial value in documentation and workflow augmentation. Their continued development, combined with strong regulatory oversight and clinical validation, will determine their long-term role in transforming healthcare systems.

VI. FUTURE WORK

The future of Large Language Model applications in healthcare documentation and clinical workflow systems is expected to evolve along multiple interconnected directions, including technical innovation, clinical integration, regulatory development, and ethical governance. One of the most important areas of future research is the development of highly specialized domain-specific LLMs trained exclusively on de-identified clinical data. While current general-purpose models demonstrate strong language capabilities, they often lack deep clinical reasoning consistency. Future models will likely incorporate multimodal learning, combining text, imaging, laboratory data, and physiological signals to produce more comprehensive patient representations. This multimodal integration will enable LLMs to support more advanced clinical reasoning tasks, such as longitudinal patient analysis, early disease detection, and personalized treatment recommendations.

Another key direction is the advancement of retrieval-augmented generation (RAG) systems in clinical environments. These systems combine LLMs with structured medical knowledge bases, ensuring that generated outputs are grounded in verified clinical guidelines and up-to-date research evidence. This approach significantly reduces hallucination risks and improves factual accuracy in clinical documentation. Future research will focus on optimizing retrieval mechanisms, improving contextual relevance, and ensuring seamless integration with electronic health record systems. Additionally, reinforcement learning from clinical feedback will play a crucial role in improving model reliability, where continuous clinician input is used to refine model outputs over time.

From an implementation perspective, future clinical workflow systems will likely emphasize real-time decision support and ambient documentation. These systems will automatically capture patient–physician conversations and generate

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

structured clinical notes in real time, reducing the administrative burden on healthcare professionals. However, achieving this will require robust privacy-preserving architectures, including federated learning and on-device processing, to ensure sensitive patient data is not exposed. Moreover, explainable AI (XAI) techniques will become essential to ensure transparency in clinical decision-making processes, allowing healthcare providers to understand how and why certain outputs are generated by the model.

Ethical and regulatory frameworks will also play a central role in shaping future developments. As LLMs become more integrated into healthcare systems, regulatory bodies will need to establish clear guidelines for validation, accountability, and clinical safety. Issues such as bias mitigation, data ownership, and patient consent will need to be addressed comprehensively. Furthermore, interdisciplinary collaboration between clinicians, data scientists, and policymakers will be critical in designing safe and effective AI systems. Finally, future research should focus on long-term clinical impact studies, evaluating not only system performance but also patient outcomes, healthcare cost reduction, and clinician well-being. Ultimately, the future of LLMs in healthcare lies in building trustworthy, interpretable, and clinically validated systems that enhance—not replace—human medical expertise.

REFERENCES

1. Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., ... & Amodei, D. (2020). Language models are few-shot learners. *Advances in Neural Information Processing Systems, 33*, 1877–1901.
2. Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. *NAACL-HLT 2019*, 4171–4186.
3. Lee, J., Yoon, W., Kim, S., Kim, D., Kim, S., So, C. H., & Kang, J. (2020). BioBERT: A pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, *36*(4), 1234–1240.
4. Alsentzer, E., Murphy, J. R., Boag, W., Weng, W. H., Jin, D., Naumann, T., & McDermott, M. (2019). Publicly available clinical BERT embeddings. *Proceedings of Clinical Natural Language Processing Workshop*, 72–78.
5. Johnson, A. E. W., Pollard, T. J., Shen, L., Li-Wei, H. L., Feng, M., Ghassemi, M., ... & Mark, R. G. (2016). MIMIC-III, a freely accessible critical care database. *Scientific Data*, *3*, 160035.
6. Rajkomar, A., Oren, E., Chen, K., Dai, A. M., Hajaj, N., Liu, P. J., ... & Dean, J. (2018). Scalable and accurate deep learning with electronic health records. *npj Digital Medicine, 1*(18).
7. Shickel, B., Tighe, P. J., Bihorac, A., & Rashidi, P. (2018). Deep EHR: A survey of recent advances in deep learning techniques for electronic health record analysis. *IEEE Journal of Biomedical and Health Informatics, 22*(5), 1589–1604.
8. Topol, E. J. (2019). High-performance medicine: the convergence of human and artificial intelligence. *Nature Medicine, 25*(1), 44–56.
9. Mathew, A., & Nair, A., & Decouth, J. R. (2019). Audience Behaviour Mining Using Data Analysis. International Journal of Data Structures, 5(2), 1-7.
10. Sudarsan, V., & Sugumar, R. (2018). Building a Distributed K-Means Model using Simple K-Means of Weka.
11. Murugeshwari, B., Jayakumar, C., & Sarukesi, K. (2012). Secure Multi Party Computation Technique for Classification Rule Sharing. International Journal of Computer Applications, 55(7).
12. Mathew, A. R. (2019). Cyber-infrastructure connections and smart gird security. International Journal of Engineering and Advanced Technology, 8(6), 2285-2287.
13. Sugumar, R., & Murugeshwari, B. (2016). An Efficient MChord based Authentication for Vehicular Ad-Hoc Networks.
14. Sudhan, S. K. H. H., & Kumar, S. S. (2016). Gallant Use of Cloud by a Novel Framework of Encrypted Biometric Authentication and Multi Level Data Protection. Indian Journal of Science and Technology, 9, 44.
15. Sruthi, R. S., Ananya, S., & Murugeshwari, B. (2010). Web Based Virtual Control System Laboratory and On-Line Temperature Control of Electrophoresis Equipment using LabVIEW. International Journal of Computer Applications, 975, 8887.
16. Mathew, A. (2019). Cybersecurity infrastructure and security automation. Adv Comput: Int J (ACIJ), 10(6).
17. Sugumar, R. (2018). Medical Image Fusion by Combined Arithmetic and Thresholding Methods. EDITORS OF SPECIAL ISSUE JOURNAL, 17.
18. Balasubramanian, V., & Rajendran, S. (2019). Rough set theory-based feature selection and FGA-NN classifier for medical data classification. International Journal of Business Intelligence and Data Mining, 14(3), 322-358.
19. Brijet, Z., Kumar, B. S., & Bharathi, N. (2017). Vehicle anti-theft system using fingerprint recognition technique. Open Academic Journal of Advanced Science and Technology, 1(1), 36-41.
20. Mathew, A. R. Malware Analysis of API Calls using FPGA Hardware Level Security.

| ISSN: 2395-0560 | www.irjie.org |editor@irjie.org| A Bimonthly, Peer-Reviewed, Scholarly Journal|

|Volume 7, Issue 1, January- February 2023|

DOI:10.15680/IRJIE.2023.0701001

21. Sugumar, R. (2014). A technique to stock market prediction using fuzzy clustering and artificial neural networks.
22. Mathew, A., & Mai, C. (2018, May). Study of Various Data Recovery and Data Back Up Techniques in Cloud Computing & Their Comparison. In 2018 3rd IEEE International Conference on Recent Trends in Electronics, Information & Communication Technology (RTEICT) (pp. 2021-2024). IEEE.
23. Murugeshwari, B., Sudharson, K., Panimalar, S. P., Shanmugapriya, M., & Abinaya, M. (2020). SAFE–Secure Authentication in Federated Environment using CEG Key code.
24. Z. Brijet, N. Bharathi, G. Shanmugapriya. (2015). Design of Model Predictive Controller for Fluid Catalytic Cracking Unit. Fluid-IJCTA, 8(5), 1917-1926.
25. Singh, T. J., & Sugumar, R. (2012, December). An extensibility of THEMIS billing system for the cloud computing environment. In 2012 Fourth International Conference on Advanced Computing (ICoAC) (pp. 1-6). IEEE.
26. Mathew, A. (2020). Threat intelligence and internet of medical things (IoMT). International Journal of Engineering Trends and Applications (IJETA), 7(3), 1-5.
27. Amutha, M., & Sugumar, R. (2015). A survey on dynamic data replication system in cloud computing. International Journal of Innovative Research in Science, Engineering and Technology, 4(4), 1454-1467.
28. Sudarsan, V., & Sugumar, R. (2019). Building a distributed K-Means model for Weka using remote method invocation (RMI) feature of Java. Concurrency and Computation: Practice and Experience, 31(14), e5313.
29. Jayaraman, S., Rajendran, S., & P, S. P. (2019). Fuzzy c-means clustering and elliptic curve cryptography using privacy preserving in cloud. International Journal of Business Intelligence and Data Mining, 15(3), 273-287.
30. Brijet, Z., & Bharathi, N. (2021). Design of type-2 fuzzy logic controller for fluid catalytic cracking unit. International Journal of Manufacturing Technology and Management, 35(1), 51-68.
31. Sudhan, S. K. H. H., & Kumar, S. S. (2015). An innovative proposal for secure cloud authentication using encrypted biometric authentication scheme. Indian Journal of Science and Technology, 8(35), 1-5.
32. Mathew, A. R. Airport Cyber Security and Cyber Resilience Controls. arXiv 2019. arXiv preprint arXiv:1908.09894.
33. Sulthana, A. R., & Murugeswari, B. (2011, March). ARIPSO: Association rule interactive postmining using schemas and ontologies. In 2011 International Conference on Emerging Trends in Electrical and Computer Technology (pp. 941-946). IEEE.
34. Chiranjeevi, K. G., Latha, R., & Kumar, S. S. (2016). Enlarge Storing Concept in an Efficient Handoff Allocation during Travel by Time Based Algorithm. Indian Journal of Science and Technology, 9, 40.
35. Priya, P. S., & Sugumar, R. (2014). Multi Keyword Searching Techniques over Encrypted Cloud Data. In IJSR.
36. Suresh, T., Brijet, Z., & Sheeba, T. B. (2021). CMVHHO-DKMLC: A Chaotic Multi Verse Harris Hawks optimization (CMV-HHO) algorithm based deep kernel optimized machine learning classifier for medical diagnosis. Biomedical Signal Processing and Control, 70, 103034s
37.